## **DESS** Textile floor covering - Tiles

## Granite EcoBase<sup>™</sup>

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10 "						
Aspect	ISO 2424		Structured loop pile						
Dye method			Solution dyed						
Dimension	EN ISO 24342	50 x 50 / 19,68" x 19,68" (20 tiles per box)							
Primary backing	ISO 2424	Polyester fleece							
Secondary backing	ISO 2424		DESSO EcoBase® * - Containing at least 75% C2C positively defined recycled content						
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **						
Total thickness	ISO 1765	mm	6.5		inch	0.3			
Effective pile thickness	ISO 1766	mm	3.3		inch	0.13			
Total mass	ISO 8543	g/m²	4400		oz/yd²	129.9			
Total pile mass	ISO 2424	g/m²	920		oz/yd²	27.2			
Effective pile mass	ISO 8543	g/m²	530		oz/yd²	15.6			
Pile density	ISO 8543	g/cm³	0.161		lb/in³	0.0058			
Number of tufts	ISO 1763	/dm²	1580		/yd²	132104			
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10°						
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 2						
Dimensional stability	EN 986	%	≤ 0,2						
Impact sound reduction $\Delta L_w$	ISO 10140	dB	24						
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000	
		$\alpha_s$	0.02	0.03	0.05	0.15	0.30	0.39	
Noise reduction	ISO 354	$\alpha_{w}$	0.15						
Thermal resistance	ISO 8302	m².K/W	0.071						
Flammability	EN 13501-1	Bfl - s1 (loose laid tested)							
Prodis - GUT	www.pro-dis.info		A30AF3CD						







<sup>\*</sup> DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com

Tarkett's flooring products are to be installed in full accordance with DESSO installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. Tarkett's flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

**O** Tarkett

<sup>\*\*</sup> ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com