

Woven 6012



Woven 106012

WOVEN 6012



▲ Woven 106012

Manufacturing process	Woven face-to-face Wilton	Number of points	ca. 340.000/m²
Pile content	100% PP StainSafe®	Width	400 cm
Pile weight	ca. 1.320 gr/m²	Design Repeat	100 (W) x 100 (H) cm
Total weight	ca. 2.050 gr/m²	Light Fastness	5-6
Pile height	ca. 7,5 mm	Water resistance	4-5
Total height	ca. 10 mm	Characteristics	Heavy Domestic / General contract use
Shot density	50/10 cm	Thermal resistance	0,13 m² K/W (Tog 1,3)
Warp rate	34/10 cm	Installation	Underlay and gripper rods BS5325
Fire Class	BS4790 - Low Radius of Effects		



EAC



Onder voorbehoud van de wijzigingen van de technische specificaties - Kijk voor de uitgebreide garantievoorwaarden op www.stain-safe.com
 Sous réserve de modifications techniques - Pour le détail des conditions de garantie, rendez-vous sur www.stain-safe.com
 Unter Vorbehalt von Änderungen der technischen Daten - Detaillierte Garantiebedingungen finden Sie auf www.stain-safe.com
 All rights reserved to alter technical specifications - For detailed warranty conditions, see www.stain-safe.com

Wakkensteenweg 2, 8710 Sint-Baafs-Vijve, Belgium, T +32 (0)56 62 22 11, info@baltagroup.com, www.baltagroup.com