

QUALITY
ORDER CODE

DATE: 15/11/2018
REPLACES: 4/09/2018

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1

BS 4790

SERENADE SUPERB SMB
SSB

± 400 & 500
COLLECTION
1/8" SAXONY

SOLUTION DYED

PP

WOVEN

SMART BACK

± 2.785
± 3.650

± 15,5
± 18,0
± 151.200
± 31,50
± 48,00

±
±

±

✓
✓

Cl. 21
Domestic Moderate/Light



LC5



Efl



QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m²/KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

AVAILABLE
FROM

COLOURS



<u>SMB 400</u>	SSB	<u>SMB 500</u>
0230	FLAX	0230
0270	ALMOND	0270
0430	BAMBOO MAT	0430
0440	IVORY	0440
0450	SAND	0450
0460	HEMP	0460
0850	MOONBEAM	0850
0860	GRANITE	0860
0870	SILVER	0870
0880	PEARL	0880

WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

SERENADE SUPERB SMB

± 25

±

± 2,2

≤

≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3

18 EN 14041
DOP 1038-125902

LANO NV - Venetiëlaan 33
B-8530 HARELBEKE
Floor carpets to use in
buildings

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE