

QUALITY
ORDER CODE

DATE: **11/09/2018**
REPLACES: 21/12/2010

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

CORINDO SB
COI

± 400
COLLECTION
1/10" LOOP PILE

PIECE DYED

PA

NON WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 720
± 1.880

± 4,5
± 7,0
± 102.440
± 39,40
± 26,00

±
±

± 48-30
PILE IN

✓

✓

✓

✓

✓

✓

✓

ANTISTATIC

✓

✓

✓

DBC3FD6F

22113
Z-156.601-957 - PA 6 / 111 / FS

04/009
U3P3E1C0

✓

CL. 33
Commercial Heavy



LC2 

Bfl-s1 
LOW RADIUS

