

QUALITY
ORDER CODE

DATE: **18/06/2018**
REPLACES: 18/12/2017

WIDTH (±) cm

TYPE

GAUGE AND TYPE

TEXTURING

DYEING/PRINT METHOD

PILE COMPOSITION

FIBRE BRAND

WOOLMARK

MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²

TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm

TOTAL HEIGHT (±) mm

NUMBER OF KNOTS (±) m²

STITCHES OVER WIDTH (±) / 10 cm

STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm

REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m

PILE IN/OUT

LANO CLASSIFICATION

BEDROOM

LIVING ROOM

OFFICE

CASTOR ROLLCHAIRS DOMESTIC USE

CASTOR ROLLCHAIRS PROFESSIONAL USE

STAIRS DOMESTIC USE

STAIRS PROFESSIONAL USE

ELECTROSTATIC BEHAVIOUR

UNDERFLOOR HEATING

BATH ROOM

NON-FRAY

PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER

DIBT

UPEC n°

CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION

CLASSIFICATION BS7131

BERGAMO KT
BER

± 400 & 500
COLLECTION
5/64" CUT PILE

PIECE DYED

PA 6.6

WOVEN

TEXTILE BACKING C-BACK

± 705

± 1 850

± 5,5

± 8,5

± 388 080

± 50,40

± 77,00

±

±

± 25

PILE IN

✓

✓

✓

✓

✓

✓

✓

ANTISTATIC

✓

37E84BAD

18/316

U3P3E1C0

Cl. 32

Commercial General



LC2 

Bfl-s1 

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 20



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

±

THERMAL RETENTION

(±) m²/KW

ISO 8302

±



TOG rating

(±)

± 1,6

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤ 2



SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN WITH EC1 APPROVED
ADHESIVE - SHORT PIN MUSHROOM TAPE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

AVAILABLE
FROM

COLOURS

KT 400	BER	KT 500
001	ELDER 1	001
030	DOVE	030
060	HEATHER	060
070	VIOLET	070
090	MUSTANG	090
100	RUBY	100
110	CARMINE	110
130	ROSE	130
140	OLD ROSE	140
150	SAHARA	150
220	ACORN	220
290	SEPIA	290
340	AMBER	340
370	GOLD	370
440	IVORY	440
450	SAND	450
530	APPLE	530
580	RESEDA	580
670	PETROL	670
700	NAVY	700
710	ATLANTIC	710
730	AZURE	730
740	OCEAN	740
760	WEDGWOOD	760
780	STEEL	780
790	MIDNIGHT	790
800	DARK TEAL	800

KT 400	BER	KT 500
810	CHARCOAL	810
840	MOONSHINE	840
860	GRANITE	860
870	SILVER	870
880	PEARL	880

(32)

(32)



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

