

Manufacturing process Tufting 1/10" Cut pile	Méthode de fabrication Tuftée 1/10" velours coupé	Herstellungsverfahren Getuftet 1/10" Schnittpol	Fabricagemethode Getuft 1/10" gesneden pool
Pile content 100% PP Stainsafe [®]	Composition du velours 100% PP Stainsafe [®]	Polmaterial 100% PP Stainsafe [®]	Poolsamenstelling 100% PP Stainsafe [®]
Total weight Ca. 4.300 g/m ²	Poids total Ca. 4.300 g/m ²	Gesamtgewicht Ca. 4.300 g/m ²	Totaal gewicht Ca. 4.300 g/m ²
Pile weight Ca. 650 g/m ²	Poids du velours Ca. 650 g/m ²	Polgewicht Ca. 650 g/m ²	Poolgewicht Ca. 650 g/m ²
Total height Ca. 7,2 mm	Hauteur totale Ca. 7,2 mm	Gesamthöhe Ca. 7,2 mm	Totale hoogte Ca. 7,2 mm
Pile height Ca. 4,7 mm	Hauteur du velours Ca. 4,7 mm	Floröhe Ca. 4,7 mm	Poolhoogte Ca. 4,7 mm
Tuft density Ca. 185.650/m ²	Nombre de touffes Ca. 185.650/m ²	Noppenzahl Ca. 185.650/m ²	Aantal noppen Ca. 185.650/m ²
Size 50 x 50 cm	Dimensions 50 x 50 cm	Abmessung 50 x 50 cm	Afmetingen 50 x 50 cm
Packaging 5 m ²	Emballage 5 m ²	Verpackung 5 m ²	Verpakking 5 m ²
Antistatique < 2 kV	Antistatique < 2 kV	Antistatisch < 2 kV	Antistatisch < 2 kV
Fire class E _{FL} (EN 13501-1)	Classement feu E _{FL} (EN 13501-1)	Brandverhaltensklasse E _{FL} (EN 13501-1)	Brandklasse E _{FL} (EN 13501-1)
Fastness to light 5-6	Solidité à la lumière 5-6	Lichtechtheit 5-6	Lichtechtheid 5-6
Water fastness 3-4	Solidité à l'eau 3-4	Wasserechtheit 3-4	Waterechtheid 3-4



INTRIGO



Luxury Carpet Tiles



▲ 640



▲ 790



▲ 810



▲ 880




▲ 380



▲ 160



▲ 980



▲ 950