

TIARA

(Unique)

Specification

Construction	Nylon Printed Carpet
Component	100% Nylon 6
Design	All cut pile
Dye method	Chromojet printed
Pile height	6mm
Pile weight	800 g/sqm
Gauge	1/10"
Primary backing cloth	PP Cloth
Secondary backing	Action back
Yarn treatment	Anti-static filament
Yarn treatment	3M Scotchguard
Total thickness	8-9mm
Total carpet weight	1,700 g/sqm
Min order quantity	300sqm per design/color
Carpet width	3.66m or 4m

Performance

US Standard			
Item	Code	Result	Criteria
AACHEN Dimensional stability	ITTS 004	CT4: -.0025 MT4: -.0050	.027max. CT4 & MT4
Electrostatic propensity	AATCC 134-1996	neg.0.3 neg.1.1	neg. 3.5
Tuft bind of pile	ASTM D 1335	12.8lbs	8.0lbs. For tile backed
Accelerated soiling of pile yarn	ASTM D6540	rating:5.0	
Flooring radiant panel test	ASTM E 648-04 (NFPA 253)	0.74watts/cm2	>0.45watts/cm2 class I



GB/T 19001-2000 idt. ISO9001:2000
GB/T 19001-2004 idt. ISO14001:2004



MEMBER

3M

