




### Installation Method



Herringbone



Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** WW890 **Colour** 105383 Linen Dobby **Collection** World Woven **Backing** GlasBac®

### Product Specifications

Product Number	28240AK00
Product Construction	Tufted Pattern Loop
Yarn System	100% Recycled Content Type 6 Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt <sup>2</sup> ®
Preservative Protection	Intersept <sup>®</sup>

	Imperial	Metric
Tufted Yarn Weight	30 oz/yd <sup>2</sup>	1,017 g/m <sup>2</sup>
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.17 in	4.3 mm
Pile Thickness	0.123 in	3.1 mm
Stitches	7.5 /in	29.5 ends/10cm
Pile Density	8,780 oz/yd <sup>3</sup>	325,560.4 g/m <sup>3</sup>
Size	9.845 in x 39.38 in	25cm x 1m

### Performance Specifications

Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.9 to 2.2
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

### Environmental Specifications

Total Recycled Content	78%
Recycled Content (Post Industrial)	66%
Recycled Content (Post Consumer)	12%
Indoor Air Quality	<a href="#">Green Label Plus #GLP0820</a>
Ingredients and Life Cycle Impacts	<a href="#">Environmental Product Declaration</a>
Other Environmental Claims	3rd Party Verified Carbon Neutral <a href="#">NSF/ANSI-2440 Gold</a> - Sustainability Assessment
End Of Life	Carpet to Carpet Recycling

### Technical Information

Installation	<a href="#">See Interface Installation Guidelines online</a>
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>
Reclamation	Recyclable through ReEntry <sup>®</sup> - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Standard Backing	GlasBac <sup>®</sup>
Backing Options	GlasBac <sup>®</sup> , GlasBac <sup>®</sup> RE, CushionBac Renew <sup>™</sup>
Tile Size Options	25cm x 1m, 50cm x 50cm
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>