

GROOVE

Heavy Contract FRS Textured Loop Pile Carpet Tiles

Specification:

| | |
|-------------------------|--------------------------------|
| Yarn Type: | 100% Noval Solution Dyed Nylon |
| Tile Size: | 50cm x 50cm |
| Pile Height: | 2.5 to 4.5mm |
| Total Thickness: | 5.0 to 7.0mm |
| Pile Weight: | 740g/m ² |
| Machine Gauge: | 1/12 (47.24 per 10cm) |
| Stitch Count: | 38 per 10cm |
| Tuft Density: | 179,512 |
| Total Weight: | 4655g/m ² |
| Lock Coat: | Antistatic SBR |
| Tile Backing: | Anchorite 'B' |
| Suggested Laying Method | Tessellated or Broadloom |

Wear Characteristics



Castor Chair Test: BS EN 985: TEST A:2001

Pass – Suitable for use in areas where castor chairs are used

Hexapod: BS ISO 10361:METHOD B: 2000

3 to 4

Static Loading – BS 4939:1987(1996)

Recovery > 85% (24 hrs.)

Dynamic Load – BS ISO 2094:1999

Loss < 20% (1000 impacts)

Flame Resistance



Hot Metal Nut Test: BS 4790

Low radius of char -according to BS5287:1998 (1996)

ANSI/ASTM E648 00/NFPA253 1995

Grade 1

BS EN 13501:2002

Class C_{fl}-s1

Colour Fastness



Shampoo: BS1006: UK-TB: 1990

Minimum grade 4 to 5

Light Fastness: BS1006: B2

Minimum grade 6

Static Protection



Stroll Test: BS ISO 6356:2000

<2kV

August 2007

All Burmatex tile products contain up to 10% of post-manufacture recycled waste in the tile backings.

Burmatex are pleased to offer a 10 year warranty on this product